

## OTOKLAV CİHAZI

AUTOCLAVE 2 lt



### ÜRÜN TEKNİK ÖZELLİKLERİ

### TECHNICAL DETAILS

2 litre iç hacimli  
Max. Çalışma Basıncı = 260 kg/cm<sup>2</sup>  
Max. Çalışma Sıcaklığı = 260 °C  
Manyetik kaplinli karıştırma mili ve  
0 – 1500 dev/dak arası kademesiz ayarlanabilir  
karıştırıcı hızı.  
Ceket tipi tam izolasyonlu elektrik fırını, hassas  
dijital ısı kontrol cihazı.  
Gövde ve kapak yekpare kaynaksız AISI 316 kalite  
korozyon ve aside dayanıklı paslanmaz çelikten  
imal edilmiş olarak. Ani soğutma spirali, basınç  
altında iken içerden numune alma vanası, yüksek  
ve alçak basınç manometreleri ile tekmil

Max. Operating Pressure = 260 kg/cm<sup>2</sup> - Max.  
Operating Temperature = 260 °C  
Internal Volume 2 liter. Infinitely adjustable  
internal mixing through magnedrive shaft  
between 0-1500 rpm.  
Fully insulated jacket-type electric furnace, preci-  
sion digital temperature controller.  
The cylindrical main body and the top cover are  
made of AISI 316 stainless steel, without welding  
.Equipped with a quick cooling spiral tube heat  
exchanger made of AISI 316 stainless steel tube  
with suitable end connections for water circulation.  
Also equipped with a sample outlet valve under  
pressure (without opening the cover).